



T Series Pin Vane Pumps with High Pressure






Products Introduction

This product use float side panel, vane of dowel pin structure, technics of double-edged vane and wholly new low noise technology cure to process stator. Compared with other dosing vane pump, its advantages are:

- High working pressure – it can reduce the size of hydraulic actuator ,control valves and tubing, which makes for cutting the cost, you can also extend its working life by lowering the working pressure.
- High efficiency – both volumetric and mechanical efficiency are higher than 94%,so it helps to raise productivity, reduce heating and running cost.
- Smaller pressure fluctuation – it will reduce the noise of tubing and extend operating life of other hydraulic element.



- High fouling resistance –using vane of double lips structure provides high fouling resistance and long operation life
- Low noise – the vane structure of dowel pin which can decrease the force on the stator which comes from vane efficiently. We also adopt wholly new low noise technology stator, so it produces little noise. And the T*L series pumps with thicker body make for reducing mechanical amplitude and lower noise.
- Wide speed range – combining pump core which has large displacement with smaller pump body to produce large displacement pumps with low noise.

In particular, this series of products is suitable for cutting machinery plastic machinery, leather machinery, pressing machinery, engineering machinery, metallurgical machinery and so on.



Application Specification

Initial Startup Checks

Check the accuracy of design and installation of hydraulic station:

- Make the distance between inlet and outlet as long as possible.
- The pipe orifice of inlet and outlet should be slope and the section eagle should be greater than or equal to 45° , in order to increase passage section ,slower velocity, recommend velocity in inlet is between 0.5m/s and 1.9m/s. and in outlet is below 6m/s.
- Confirm the oil ports are below the oil level in fuel tank in the worst-case scenario (example: all of hydraulic cylinder pistons are extending to the extreme position),
- Specifications of the air filter should be threes greater than the maximum return flow.
- Set the release valve for exhaust on oil returning pipe; and you can also slightly loosen the joint of pump outlet to vent until there are no bubbles in the oil spill, then you can tighten the joint to produce the same effect.

Notice: This method is suitable for low pressure and you should make sure the pressure will not rise.

Initial start:

- Check the accuracy of the location of oil ports.
- Pump should vent well when injecting oil.
- Inching running the pump for a few seconds, and you should loosen the relief valve on the outlet to reach the minimum pressure.
- Do not drive the pump in a high speed and pressure before the check is over.



Application Specification

Shaft&Coupling

Coupling&spline hole

- The spline hole of the coupling should be floating and automatically be in center, so as to reducing wear, and the slope deviation of two spline shaft is less than or equal to $\pm 0.05/25.4\text{mm}$ (deviation of dial indicator)
- Spline hole must be lubricated by molybdenum disulfide lithium-based grease or other similar grease.
- Coupling demand heat treatment to reach the hardness of 29~45HRC.
- The specification of spline hole should meet the one-level standards in SAE-J498b(1971) ,as the coordination is flat root and lateral teeth.

Flat spline shaft

- T7, T67 and T6 series vane pumps provide a high strength key, hence you must use it when installing or changing the pump , or you can use a new key whose hardness is 27~34HRC and edge angle is $0.8\sim 1^{\circ}45^{\circ}$ to avoid the circular angle in the key slot when it' necessary to change keys。

The load of shaft

- The construction of requirement of flat spline shaft is the same to the spline shaft's.

This series products is only allowed to bear transmission load, do not apply radial and axial load.



Application Specification

Hydraulic Fluid

Classification Of Hydraulic Fluid

HF-0、 HF-2	: anti-wear hydraulic oil
HF-1	: common hydraulic oil
HF-3	: water in oil emulsion
HF-4	: water-glycol hydraulic fluid
HF-5	: synthetic hydraulic fluid

Recommended hydraulic Oil

We recommend anti-wear hydraulic oil for all the highest rated working parameter and performance parameter are based on the test using the anti-wear hydraulic.

Other Hydraulic Oil

When using other hydraulic oil, you should lower the Max. rated operating parameters of pump. in some situations, you have to raise the min. pressure of the inlet, and you can see related sections for details.

Viscosity

Uppermost Viscosity (cold start mode、 low speed and pressure).....	860cSt
Uppermost Viscosity (full speed and high pressure).....	108cSt
Best viscosity (longest working time)	30cSt
Minimum viscosity (full speed and high pressure, for HF-1、 HF-3、 HF-4、 HF-5)	18cSt
Minimum viscosity (full speed and high pressure, for HF-0、 HF-2)	18cSt

Viscosity Index

The lowest index: 90V.L. high index can extent operating temperature range but it can also shorten the life of working liquid.



Application Specification

Operating Temperature

the operating temperature mainly depends on viscosity ,also it's related to seal material, and for standard seals , its range is from -30°C to 90°C .

Max. Temperature

- HF-0、HF-1、HF-2.....+100°C
- HF-3、HF-4.....+50°C
- HF-5.....+70°C
- Biodegradable hydraulic oil (organic grease and rapeseed oil-based grease)...+100°C

Min. liquid temperature (also depends on Max. viscosity)

- HF-0、HF-1、HF-2、HF-5.....-18°C
- HF-3、HF-4.....+10°C
- Biodegradable hydraulic oil(organic grease and rapeseed oil-based grease)....-20°C

Operating temperature and Viscosity

Operating temperature depends on the viscosity, variety of working liquid and property of pump. Usually ,we used the most suitable viscosity. And when the hydraulic pump cold start, drive it in conditions of low speed and low pressure to heat up the liquid to a suitable temperature, then operate it under full power.

Cleanliness of working fluid

Solid contamination level of oil is required to be lower than level 8 in NAS1618 (or ISO 18/14) and you can use the filter whose filtrate precision is 25 μm(or $\beta_{100} \geq 100$)

Solid contamination level should meet the need of Min. suction pressure. Recommended filter screen 100 mesh (149μm), and you'd better enlarge the filter size or remove filter when the system demand cold start or using fire resistant oil.

Water pollution of working fluid

Mineral oil-based grease.....0.1%

Synthetic hydraulic fluid crank case oil and biodegradable hydraulic fluid.....0.05%

The system demand dehydration when moisture content is too high.



ГИДРООТВЕТ

доступная гидравлика

技术参数 (单联泵)

Technical parameters (single pump)

规格系列 Specifications Series	泵芯规格 PC specification	理论排量 Displacement q_i	最高转速 Max. speed	最高压力 Max. pressure											
				HF-0, HF-3		HF-1, HF-4, HF-5		HF-3							
				HF-1	HF-4	间歇	连续	间歇	连续	间歇	连续				
				Intermittent	Continuous	Intermittent	Continuous	Intermittent	Continuous	Intermittent	Continuous				
T67B T7BL	B03	10.8	600	2800	1800	320	290	240	210	175	140				
	B05	17.0													
	B06	21.2													
	B08	26.2													
T6C T6CL	B10	34.0		2500	2800	300	275								
	B12	37.0													
	B14	46.0													
	B17	58.0													
T6D T7D T7DS T7DL	003	10.8	600	2800	1800	275	240	210	175	175	140				
	005	17.0													
	006	21.2													
	008	26.2													
	010	34.0		2500	2800	210	160	160	160	160	160				
	012	37.0													
	014	46.0													
	017	58.0													
T6E T7E T7ES T7EL	020	63.5	600	3000	1800	300	250	240	210	175	175				
	022	70.0													
	025	79.0													
	028	89.0													
	031	100.0		2800	2500	280	230	210	175	175	175				
	035	113.4													
	038	120.6													
	042	137.5													
	045	145.7		2500	2200	240	210	210	175	175	175				
	050	158.0													
	052	164.8													
	054	171.0													
T6E T7E T7ES T7EL	057	183.3	600	2200	1800	240	210	210	175	175	175				
	062	196.7													
	066	213.3													
	072	227.1													
	085	268.7													

注: HF-0, HF-2=石油基抗磨液压油;
 HF-1=石油基液压油(非抗磨);
 HF-3=油包水乳化液;
 HF-4=水乙二醇;
 HF-5=合成液压油(磷酸脂液等)。

Note: HF-0, HF-2= Anti-wear hydraulic oil
 HF-1= General hydraulic oil
 HF-3= Water in oil emulsions
 HF-4= Water glycol fluid
 HF-5=Synthetic hydraulic fluid (phosphate ester etc.)



技术参数 (双联泵)

Technical parameters (Double pumps)

规格系列 Specifications Series	泵芯规格 PC specification	理论排量 Displacement q_i	最高转速 Max. speed	最高压力 Max. pressure											
				最低转速 Min. speed	HF-0, HF-3		HF-1, HF-4, HF-5		HF-3						
					HF-0	HF-3	HF-1	HF-4	HF-5	HF-3					
					间歇	连续	间歇	连续	间歇	连续					
				mL/r	r/min	r/min	bar	bar	bar	bar	bar				
T67 <u>BB</u> T67 <u>CB</u> T67 <u>DB</u> T7 <u>DBS</u> T7 <u>EBS</u> T7 <u>BBL</u>	B03	10.8	600	2200	1800	300	275	240	210	175	140				
	B05	17.0													
	B06	21.2													
	B08	26.2													
	B10	34.0				280	240								
	B12	37.0													
	B14	46.0													
	B17	58.0													
T6 <u>CC</u> T67 <u>CB</u> T67 <u>DC</u> T67 <u>EC</u> T6 <u>DC</u> T6 <u>EC</u> T6 <u>CCL</u> T7 <u>CBL</u>	003	10.8	600	2200	1800	275	240	210	175	175	140				
	005	17.0													
	006	21.2													
	008	26.2													
	010	34.0													
	012	37.0													
	014	46.0													
	017	58.0				210	160	160	160	160	160				
	020	63.5													
	022	70.0													
	025	79.0													
	028	89.0													
	031	100.0													
	014	44.0													
T7 <u>DBS</u> T6 <u>DC</u> T67 <u>DC</u> T6 <u>ED</u> T7 <u>EDS</u>	017	55.0	600	2200	1800	250	210	240	210	175	140				
	020	66.0													
	022	70.3													
	024	81.1													
	028	90.0													
	031	99.2													
	035	113.4				210	160	210	175	175	140				
	038	120.6													
	042	137.5													
	045	145.7													
	050	158.0													
	042	132.3													
T7 <u>EBS</u> T6 <u>EC</u> T6 <u>ED</u> T7 <u>EDS</u>	045	142.4	600	2200	1800	240	210	210	175	175	140				
	050	158.5													
	052	164.8													
	054	171.0													
	057	183.3													
	062	196.7				90	75	75	75	75	75				
	066	213.3													
	072	227.1													
	085	268.7													

注: HF-0, HF-2=石油基抗磨液压油;
 HF-1=石油基液压油(非抗磨);
 HF-3=油包水乳化液;
 HF-4=水乙二醇;
 HF-5=合成液压油(磷酸脂液等)。

Note: HF-0, HF-2= Anti-wear hydraulic oil
 HF-1= General hydraulic oil
 HF-3= Water in oil emulsions
 HF-4= Water glycol fluid
 HF-5=Synthetic hydraulic fluid (phosphate ester etc.)



ГИДРООТВЕТ

доступная гидравлика

技术参数 (允许的最低吸口绝对压力 bar)

Technical parameters (Allow the Min. Suction absolute pressure, bar)

规格系列 Specifications Series	泵芯规格 PC specification	转速 speed r/min									泵芯规格 PC specification						
		1200	1500	1800	2100	2200	2300	2500	2800	3000							
B	B03	0.80	0.80	0.80	0.80	0.80	0.80	0.80	0.80	0.80	B03						
	B05										B05						
	B06										B06						
	B08										B08						
	B10										0.82						
	B12										B10						
	B14										0.85						
	B17										0.90						
C	003	0.80	0.80	0.80	0.80	0.80	0.90	1.00	0.80	0.80	003						
	005										005						
	006										006						
	008										008						
	010										010						
	012										012						
	014										014						
	017										017						
D	020				0.90	0.90	1.05	1.05	0.80	0.80	020						
	022										022						
	025										025						
	028										028						
	031										031						
	014	0.80	0.80	0.80							014						
	017										017						
	020										020						
	022										022						
	024										024						
	028										028						
	031										031						
	035										035						
	038										038						
E	042	0.80	0.80	0.80	0.80	1.00	0.80	0.80	0.80	0.80	042						
	045										045						
	050										050						
	052										052						
	054										054						
	057										057						
	062										062						
	066										066						
F	072	0.85	0.85	0.95	1.00	1.09	0.80	0.80	0.80	0.80	072						
	085										085						
	090										090						

- 表中所列的数值是在以粘度为 10~65cSt 的石油基液压油为工作介质时，在吸口连接法兰处测得的绝对压力，吸口绝对压力相对于大气压的压差不得大于 0.2bar，以防止产生气穴。
- 对于 HF-3 (油包水乳化液) 和 HF-4 (水乙二醇) 吸口最低绝对压力应为上列数值乘以 1.25；对 HF-5 (合成液压油) 应乘以 1.35；而对于有机脂类或菜籽油基液压油，则应乘以 1.10。
- 对于双联泵，吸口绝对压力应以最大规格联的参数选取。
- The values are listed in the table in the viscosity of 10 ~ 65 cSt petroleum base hydraulic oil as working medium, the suction flange measure absolute pressure, suction absolute pressure relative to the atmospheric pressure differential pressure shall not be greater than 0.2 bar, in order to prevent air pockets.
- For HF-3 (water-in-oil emulsion) and HF-4 (water glycol fluid) the Min. absolute suction pressure should be the above value multiplied by 1.25, for HF-5 (synthetic hydraulic oil) should be multiplied by 1.35, and for organic esters or rapeseed oil based hydraulic oil is multiplied by 1.10
- For double pumps, the suction pressure should be selected with the max. specification



ГИДРООТВЕТ

доступная гидравлика

型号说明 Model Code

◎ 单泵 Single Pump

T6C	-022	-1	R	00	-A	1	M0
型号 (示例) Model(example)	油口联接螺纹 Port connection threads						
系列代号 Series Code					公制 Metric units	美制 US units	
规格排量 · mL/r Displacement					M0	00(略) Omit	
轴 号 Shaft NO.					密封等级 (sealing class):		
旋转方向 (从轴端看) Direction of rotation(view from shaft end)	1:S1-丁晴橡胶: 石油基液压油 (省略) S1-NBR:petroleum base and hydraulic oil (Omit)				5: S5-氟橡胶: 石油基与抗燃液压油 S5-FPM:petroleum based and fire resistant hydraulic oil.		
油口方向组合: S=进油口 P=出油口 Ports directional combination : S= inlet P= outlet							
代号 code Standard features	00 (标准配置) Standard features	01	02	03			
油口方向 ports direction					设计序号 Design number A: 由生产商给定 A: Given by the manufacturer		




ГИДРООТВЕТ

доступная гидравлика


安装联接尺寸 Install Connection Dimensions

◎ T67B、T6C 单泵/ T67B、T6C Single Pump

重量 weight:15.7 kg



轴的最大扭矩 mL/r × bar Max. torque of shaft mL/r × bar	
轴号 (Shaft No.)	q × p _{max}
1	16340
2	14300
3	20600
4	21800



渐开线花键SAE BB J498-b 1级精度 平齿根 齿侧配合 齿数 15 齿节 16/32 压力角 30° 大径 $\phi 25_{-0.27}^0$
Involute spline SAE BB J498-b Class 1
Flat root Side fit spline Number of teeth 15
Pitch 16/32
Pressure angle 30°
Major diameter $\phi 25_{-0.27}^0$

渐开线花键SAE B J498-b 1级精度 平齿根 齿侧配合 齿数 13 齿节 16/32 压力角 30° 大径 $\phi 21.8_{-0.27}^0$
Involute spline SAE B J498-b Class 1
Flat root Side fit spline Number of teeth 15
Pitch 16/32
Pressure angle 30°
Major diameter $\phi 21.8_{-0.27}^0$

平键 $4.75_{-0.04}^0$ Straight key
32
58.2
M8 × 16
$\phi 22.22_{-0.020}^{+0.05}$
24.35




ГИДРООТВЕТ

доступная гидравлика


安装联接尺寸 Install Connection Dimensions

◎ T6D、T7DS 单泵/ T6D、T7DS Single Pump

重量 weight:26.0 kg



轴的最大扭矩 mL/r × bar	
Max. torque of shaft mL/r × bar	
轴号 (Shaft No.)	q × p _{max}
1	43240
2	34590
3	61200
4	61200



4号轴

No4. Shaft

77.7
48
渐开线花键NO SAE J498-b 1级精度 平齿根 齿侧配合 齿数 14 齿节 12/24 压力角 30° 大径 Φ 31.2 ⁰ _{-0.24}
Involute spline NO SAE J498-b Class 1 Flat root Side fit spline Number of teeth 14 Pitch 12/24 Pressure angle 30° Major diameter Φ 31.2 ⁰ _{-0.24}

3号轴

No3. Shaft

55.2
38
渐开线花键SAE C J498-b 1级精度 平齿根 齿侧配合 齿数 14 齿节 12/24 压力角 30° 大径 Φ 31.2 ⁰ _{-0.24}
Involute spline SAE C J498-b Class 1 Flat root Side fit spline Number of teeth 14 Pitch 12/24 Pressure angle 30° Major diameter Φ 31.2 ⁰ _{-0.24}

2号轴 (NO SAE)

No2. Shaft

平键 7.94 ⁰ _{-0.05} Straight key
40
M10 × 20
Φ 31.75 ⁰ _{-0.025}
35.27




ГИДРООТВЕТ

доступная гидравлика


安装联接尺寸 Install Connection Dimensions

◎ T6E、T7ES 单联泵/ T6E、T7ES Single Pumps

重量 weight:43.3 kg




4号轴
No4. Shaft



渐开线花键SAE CC
J498-b 1级精度
平齿根 齿侧配合
齿数 17
齿节 12/24
压力角 30°
大径 $\phi 37.56^{+0}_{-0.25}$

Involute spline SAE CC
J498-b Class 1
Flat root Side fit spline
Number of teeth 17
Pitch 12/24
Pressure angle 30°
Major diameter $\phi 37.56^{+0}_{-0.25}$


3号轴
No3. Shaft



渐开线花键SAE C
J498-b 1级精度
平齿根 齿侧配合
齿数 14
齿节 12/24
压力角 30°
大径 $\phi 31.2^{+0}_{-0.24}$

Involute spline SAE C
J498-b Class 1
Flat root Side fit spline
Number of teeth 14
Pitch 12/24
Pressure angle 30°
Major diameter $\phi 31.2^{+0}_{-0.24}$

2号轴 (NO SAE)
No2. Shaft



平键 $9.54^{+0}_{-0.05}$
Straight key
M10 × 20
 $\phi 38.1^{+0}_{-0.025}$
42.36




ГИДРООТВЕТ

доступная гидравлика

安装联接尺寸 Install Connection Dimensions

◎ T7BL、T6CL 单联泵/ T7BL、T6CL Single Pumps 重量 weight:19.5 kg



4号轴

No4. Shaft

45.5	24.5
渐开线花键SAE BB J498-b 1级精度 平齿根 齿侧配合 齿数 15 齿节 16/32 压力角 30° 大径 $\Phi 25^0_{-0.27}$	
Involute spline SAE BB J498-b Class 1	
Flat root Side fit spline Number of teeth 15	
Pitch 16/32	
Pressure angle 30°	
Major diameter $\Phi 25^0_{-0.27}$	

3号轴

No3. Shaft

40.7	24.5
渐开线花键SAE B J498-b 1级精度 平齿根 齿侧配合 齿数 13 齿节 16/32 压力角 30° 大径 $\Phi 21.8^0_{-0.27}$	
Involute spline SAE B J498-b Class 1	
Flat root Side fit spline Number of teeth 15	
Pitch 16/32	
Pressure angle 30°	
Major diameter $\Phi 21.8^0_{-0.27}$	

2号轴 (NO SAE)

No2. Shaft

32	3.6
平键4.75 ⁰ _{-0.04} Straight key	
58.9	24.35
Φ 22.22 ^{+0.005} / _{-0.020}	
Φ 22.22 ^{+0.005} / _{-0.020}	




ГИДРООТВЕТ

доступная гидравлика

安装联接尺寸 Install Connection Dimensions


◎ T7DL 单联泵 T7DL/ Single Pumps

重量 weight:40 kg




4号轴

No4. Shaft




3号轴

No3. Shaft



2号轴 (NO SAE)

No2. Shaft






ГИДРООТВЕТ

доступная гидравлика


安装联接尺寸 Install Connection Dimensions

◎ T7EL 单联泵 T7EL/ Single Pumps

重量 weight:51.5 kg



轴的最大扭矩 mL/r × bar Max. torque of shaft mL/r × bar	
轴号 (Shaft NO.)	q × p _{max}
1	54500
2	34590
3	61200
4	61200



4号轴 NO. 4 Shaft		3号轴 NO. 3 Shaft		2号轴 (NO SAE) NO. 2 Shaft	
62.3	31.5	55.8	34.5	40	35.27
渐开线花键SAE CC J498-b 1级精度 平齿根 齿侧配合 齿数 17 齿节 12/24 压力角 30° 大径 φ 37.56 ⁰ -0.25		渐开线花键SAE C J498-b 1级精度 平齿根 齿侧配合 齿数 14 齿节 12/24 压力角 30° 大径 φ 31.2 ⁰ -0.24		平键 7.94 ⁰ -0.05 Straight Key φ 31.75 ⁰ -0.025	
Involute spline SAE CC J498-b Class 1 Flat root Side fit spline Number of teeth 17 Pitch 12/24 Pressure angle 30° Major diameter φ 37.56 ⁰ -0.25		Involute spline SAE C J498-b Class 1 Flat root Side fit spline Number of teeth 14 Pitch 12/24 Pressure angle 30° Major diameter φ 31.2 ⁰ -0.24			



ГИДРООТВЕТ

доступная гидравлика

型号说明 Model Code

◎ 双联泵 Double Pumps

T6CC	-022	-010	-1	R	00	-A	1	00	
型号 (示例) Model(example)									
系列代号 Series Code									
轴端泵排量规格 mL/r Displacement of shaft end pump mL/r									
盖端泵排量规格 mL/r Displacement of cover end pump mL/r									
轴号 Form of drive shaft									
旋转方向 (从轴端看) Direction of rotation(view from shaftend)									
R-顺时针 (标准, 可省略) Clockwise (Standard, omit)									
L-逆时针(counter clockwise)									
油口组合方向: S=进油口 P1、P2=出油口 Ports directional combination : S= inlet P1,P2= outlet									
详见 67 页									
设计序号 Design number									
A: 由生产商给定 A:Given by the manufacturer									
密封等级(sealing class)									
1: S1-丁晴橡胶: 石油基液压油 (省略) S1-NBR: petroleum base hydraulic oil (Omit)									
5: S5-FPM: 氟橡胶: 石油基与抗燃液压油 S5-FPM: petroleum based and fire resistant hydraulic oil									

T6CC

T67BB、T67CB

	公制 Metric units				美制 US units			
	0M	W0	1M	W1	00	01	10	11
S	3" (Φ 75)	$2\frac{1}{2}$ " (Φ 63)	3" (Φ 75)	$2\frac{1}{2}$ " (Φ 63)				
P1	1" (Φ 25.4)	1" (Φ 25.4)	1" (Φ 25.4)	1" (Φ 25.4)				
P2	1"	$\frac{3}{4}$ " (Φ25.4)	1" (Φ25.4)	$\frac{3}{4}$ " (Φ19)	1" (Φ25.4)	$\frac{3}{4}$ " (Φ19)	1" (Φ25.4)	$\frac{3}{4}$ " (Φ19)

	公制 Metric units		美制 US units	
	M0	M1	00	01
S	$2\frac{1}{2}$ " (Φ 63)	$2\frac{1}{2}$ " (Φ 63)		
P1	1" (Φ 25.4)	1" (Φ 25.4)		
P2	1" (Φ25.4)	$\frac{3}{4}$ " (Φ19)	1" (Φ25.4)	$\frac{3}{4}$ " (Φ19)



ГИДРООТВЕТ

доступная гидравлика

双联泵油口方向组合 Port direction combination of double pump

00 P1-P2 	01 P1-P2 	02 S-P1-P2 	03 P1-P2 	04 P1 	05 P1 S-P2
06 P1 	07 P1-S 	08 P1-S 	09 P1-S 	10 P1 	11 P1
12 P1 	13 P1 	14 P1 	15 P1 	16 P1 	17 P1
18 P1 	19 P1 	20 P1 	21 P1 	22 P1 	23 P1
24 P1-S 	25 P1-S 	26 P1-S 	27 P1-S 	28 P1 	29 P1
30 P1 	31 P1 				




ГИДРООТВЕТ

доступная гидравлика

安装联接尺寸 Install Connection Dimensions

◎ T67BB、T67CB 双联泵/T67BB、T67CB Double Pumps 重量 weight:26.0 kg



5号轴
No5. Shaft

40.7	24.5
渐开线花键SAE B J498-b 1级精度 平齿根 齿侧配合	
齿数 13	
齿节 16/32	
压力角 30°	
大径 φ 21.8 ⁰ -0.27	
Involute spline SAE B J498-b Class 1	
Flat root Side fit spline	
Number of teeth 15	
Pitch 16/32	
Pressure angle 30°	
Major diameter φ 21.8 ⁰ -0.27	

3号轴
No3. Shaft

45.5	24.5
渐开线花键SAE BB J498-b 1级精度 平齿根 齿侧配合	
齿数 15	
齿节 16/32	
压力角 30°	
大径 φ 25.0 ⁰ -0.27	
Involute spline SAE BB J498-b Class 1	
Flat root Side fit spline	
Number of teeth 15	
Pitch 16/32	
Pressure angle 30°	
Major diameter φ 25.0 ⁰ -0.27	

2号轴 (SAE BB)
No2. Shaft

平键 6.35 ⁰ -0.05 Straight key
40
2.8
71.9
M8 × 16 M8 × 16 Φ 25.4 ⁰ -0.025 28.2

轴的最大扭矩 mL/r × bar Max. torque of shaft mL/r × bar	
轴号 (Shaft NO.)	$\Sigma (q \times p_{max})$
1	14300
2	21420
3	32670
5	20600





ГИДРООТВЕТ

доступная гидравлика

安装联接尺寸 Install Connection Dimensions

◎ T6CC 双联泵/T6CC Double Pumps

重量 weight:26.0 kg




	D2=φ 25.4	D2=φ 19
A	52.4	47.7
B	26.2	22.2
C	74.7	76.2

	D=φ 75	D=φ 63
F	106.2	88.9
G	62	50.8

出油口 D2
Outlet

Inlet




5号轴
No5. Shaft

40.7	24.5
渐开线花键SAE B	
J498-b 1级精度	
平齿根 齿侧配合	
齿数 13	
齿节 16/32	
压力角 30°	
大径 φ 21.8-0.27	
Involute spline SAE B	
J498-b Class 1	
Flat root Side fit spline	
Number of teeth 15	
Pitch 16/32	
Pressure angle 30°	
Major diameter φ 21.8-0.27	

3号轴
No3. Shaft

45.5	24.5
渐开线花键SAE BB	
J498-b 1级精度	
平齿根 齿侧配合	
齿数 15	
齿节 16/32	
压力角 30°	
大径 φ 25-0.27	
Involute spline SAE BB	
J498-b Class 1	
Flat root Side fit spline	
Number of teeth 15	
Pitch 16/32	
Pressure angle 30°	
Major diameter φ 25-0.27	

2号轴 (SAE BB)
No2. Shaft



轴的最大扭矩 mL/r × bar	
轴号 (Shaft No.)	Σ (q × p _{max})
1	14300
2	21420
3	32670
5	20600



ГИДРООТВЕТ

доступная гидравлика



安装联接尺寸 Install Connection Dimensions

◎ T67DB、T6DC、T7DBS、T67DC 双联泵



重量: 38.6 kg

T67DB、T6DC、T7DBS、T67DC Double Pumps

weight: 38.6 kg



轴的最大扭矩 mL/r × bar Max. torque of shaft mL/r × bar	
轴号 (Shaft No.)	Σ (q × p _{max})
1	43240
2	34590
3	61200
4	61200
5	45200






ГИДРООТВЕТ


доступная гидравлика

安装联接尺寸 Install Connection Dimensions


◎ T7EBS、T6EC 双联泵/T7EBS、T6EC Double Pumps 重量 weight:55.0 kg



轴的最大扭矩 mL/r × bar Max. torque of shaft mL/r × bar	
轴号 (Shaft No.)	$\Sigma (q \times p_{max})$
1	54500
2	34590
3	61200
4	61200




4号轴
No4. Shaft



渐开线花键SAE CC
J498-b 1级精度
平齿根 齿侧配合
齿数 17
齿节 12/24
压力角 30°
大径 $\phi 37.56^{+0}_{-0.25}$

Involute spline SAE CC
J498-b Class 1
Flat root Side fit spline
Number of teeth 17
Pitch 12/24
Pressure angle 30°
Major diameter $\phi 37.56^{+0}_{-0.25}$


3号轴
No3. Shaft



渐开线花键SAE C
J498-b 1级精度
平齿根 齿侧配合
齿数 14
齿节 12/24
压力角 30°
大径 $\phi 31.2^{+0}_{-0.24}$

Involute spline SAE C
J498-b Class 1
Flat root Side fit spline
Number of teeth 14
Pitch 12/24
Pressure angle 30°
Major diameter $\phi 31.2^{+0}_{-0.24}$

2号轴 (NO SAE)
No2. Shaft



平键 $7.94^{+0}_{-0.05}$
Straight key




ГИДРООТВЕТ

доступная гидравлика

安装联接尺寸 Install Connection Dimensions

◎ T6ED、T7EDS 双联泵/T6ED、T7EDS Double Pumps 重量 weight:66.0 kg





ГИДРООТВЕТ

доступная гидравлика



安装联接尺寸 Install Connection Dimensions

◎ T7BBL、T7CBL、T6CCL 双联泵

重量:34.5 kg

T7BBL、T7CBL、T6CCL Double Pumps

weight:34.5 kg



5号轴 No5. Shaft	
40.7	24.5
渐开线花键SAE B J498-b 1级精度 平齿根 齿侧配合 齿数 13 齿节 16/32 压力角 30° 大径 $\phi 21.8^0_{-0.27}$	
Involute spline SAE B J498-b Class 1 Flat root Side fit spline Number of teeth 15 Pitch 16/32 Pressure angle 30° Major diameter $\phi 21.8^0_{-0.27}$	

3号轴 No3. Shaft	
45.5	24.5
渐开线花键SAE BB J498-b 1级精度 平齿根 齿侧配合 齿数 15 齿节 16/32 压力角 30° 大径 $\phi 25^0_{-0.27}$	
Involute spline SAE BB J498-b Class 1 Flat root Side fit spline Number of teeth 15 Pitch 16/32 Pressure angle 30° Major diameter $\phi 25^0_{-0.27}$	

2号轴 (SAE BB) No2. Shaft	
平键 6.35 ⁰ _{-0.05}	Straight key
40	2.8
71.9	M8 × 16
$\phi 25.4^0_{-0.021}$	28.2